

Solis Solarator Series

Experience Uninterrupted Power with Solis Energy Storage Inverters

Energy Storage Inverters

S6-EH1P(3-8)K-L-PLUS-AU

Single Phase | Low Voltage



Smart Energy Management

- AI intelligently manages charging and discharging based on TOU (Time-of-Use) tariffs
- Seamless integration with VPP and EMS platforms for enhanced energy optimization



High Performance

- 200% PV input capacity to maximize solar energy utilization
- Switching time < 10ms



Flexible & Scalable

- Compatible with mainstream lithium and lead-acid batteries
- Easily expand system capacity using parallel connections and AC coupling



Simple & Fast Configuration

- Bluetooth app support for quick and easy setup

AUSTRALIA

t: +61 1800928995 e: sales@solisinverters.com.au w: solisinverters.au
+61 3 8555 9516 service@solisinverters.com.au



DATASHEET

S6-EH1P(3-8)K-L-PLUS-AU

Models	3K	3.6K	5K	6K	8K
Input DC (PV side)					
Recommended max. PV array size	6 kW	7.2 kW	10 kW	12 kW	16 kW
Max. input voltage	500 V				
Rated voltage	330 V				
Start-up voltage	90 V				
MPPT voltage range	90 - 435 V				
Max. input current	16 A / 16 A				32 A / 32 A
Max. short circuit current	20 A / 20 A				40 A / 40 A
MPPT number / Max. input strings number	2 / 2				2 / 4
Battery					
Battery type	Li-ion / Lead-acid				
Battery voltage range	40 - 60 V				
Max. charge / discharge power	3 kW	3.6 kW	5 kW	6 kW	8 kW
Max. charge / discharge current	70 A	80 A	112 A	135 A	190 A
Communication	CAN / RS485				
Output AC (Grid side)					
Rated output power	3 kW	3.6 kW	5 kW	6 kW	8 kW
Max. apparent output power	3 kVA	3.6 kVA	5 kVA	6 kVA	8 kVA
Operation phase	1/N/PE				
Rated grid voltage	230 V				
Rated grid frequency	50 Hz				
Rated grid output current	13.1 A	15.7 A	21.8 A	26.1 A	34.8 A
Max. output current	13.1 A	15.7 A	21.8 A	26.1 A	34.8 A
Power factor	> 0.99 (0.8 leading - 0.8 lagging)				
THDi	< 2%				
Input AC (Grid side)					
Input voltage range	187 - 253 V				
Max. input current	20 A	24 A	31 A	39 A	50 A
Frequency range	45 - 55 Hz				
Output AC (Back-up)					
Rated output power	3 kW	3.6 kW	5 kW	6 kW	8 kW
Max. apparent output power	2 times of rated power, 10 s				
Back-up switch time	< 10 ms				
Rated output voltage	1/N/PE, 230 V				
Rated frequency	50 Hz				
Rated output current	13.1 A	15.7 A	21.8 A	26.1 A	34.8 A
Max. AC passthrough current	35 A	35 A	40 A	40 A	50 A
THDv (@linear load)	< 2%				
Efficiency					
Max. efficiency	96.2%				
EU efficiency	94.7%				
BAT charged by PV / AC max. efficiency	95.3% / 94.5%				
BAT discharged to AC max. efficiency	94.9%				
Protection					
Ground fault monitoring	Yes				
DC reverse-polarity protection	Yes				
Integrated AFCI	Yes ⁽¹⁾				
Protection class / Over voltage category	I / II(PV and BAT), III (MAINS and BACKUP and GEN)				
General Data					
Dimensions (W × H × D)	335 × 560 × 227 mm				
Weight	22 kg			22.5 kg	
Topology	Transformerless				
Operating ambient temperature range	-40 ~ +60°C				
Ingress protection	IP66				
Noise emission (typical)	< 65 dB(A)				
Cooling concept	Natural cooling			Intelligent fan-cooling	
Max. operation altitude	4000 m				
Grid connection standard	AS 4777				
Safety / EMC standard	IEC/EN 62109-1/-2, EN 61000-6-2/-3				
Features					
DC connection	MC4 plug (PV port) / Terminal Block (BAT port)				
AC connection	Terminal Block				
Display	LED indicator & Bluetooth + APP				
Communication	RS485, CAN, Optional: Wi-Fi, GPRS, LAN				
Country of manufacture	China				

(1) Activation required.