

S5-GR3P(5-20)K-AU

Solis Three Phase Inverters



360 degree

Model:

S5-GR3P5K-AU	S5-GR3P6K-AU	S5-GR3P8K-AU	S5-GR3P9K-AU	S5-GR3P10K-AU	S5-GR3P12K
S5-GR3P13K	S5-GR3P15K	S5-GR3P17K	S5-GR3P20K		

Efficient

- Max. efficiency 98.7%
- String current up to **16A**
- Wide voltage range and low startup voltage

Safe

- IP66
- AFCI protection, proactively reduces fire risk
- Automatic voltage stabilization technology in weak grid condition

Smart

- Support export power control
- Support RS485, WiFi, GPRS
- Scan to register on SolisCloud, support remote upgrade and control

Economic

- Compact design with easy maintenance and installation
- > 130% DC/AC ratio
- Support large module with lower installation cost

Datasheet

Model Name	S5-GR3P5K-AU	S5-GR3P6K-AU	S5-GR3P8K-AU	S5-GR3P9K-AU	S5-GR3P10K-AU	S5-GR3P12K	S5-GR3P13K	S5-GR3P15K	S5-GR3P17K	S5-GR3P20K								
Input DC																		
Recommended max. PV power	6.7 kW	8 kW	10.6 kW	12 kW	13.3 kW	16 kW	17.3 kW	20 kW	22.6 kW	26.6 kW								
Max. input voltage	1100 V																	
Rated voltage	600 V																	
Start-up voltage	180 V																	
MPPT voltage range	160-1000 V																	
Max. input current	32 A / 16 A		32 A / 32 A															
Max. short circuit current	40 A / 20 A		40 A / 40 A															
MPPT number/Max. input strings number	2/2		2/4															
Output AC																		
Rated output power	5 kW	6 kW	8 kW	9 kW	10 kW	12 kW	13 kW	15 kW	17 kW	20 kW								
Rated apparent output power	5 kVA	6 kVA	8 kVA	9 kVA	10 kVA	12 kVA	13 kVA	15 kVA	17 kVA	20 kVA								
Max. apparent output power	5 kVA	6 kVA	8 kVA	9 kVA	10 kVA	12 kVA	13 kVA	15 kVA	17 kVA	20 kVA								
Max. output power	5 kW	6 kW	8 kW	9 kW	10 kW	12 kW	13 kW	15 kW	17 kW	20 kW								
Rated grid voltage	3/N/PE, 230 V / 400 V																	
Rated grid frequency	50 Hz																	
Rated grid output current	7.9 A	9.5 A	12.7 A	14.3 A	15.9 A	19.1 A	20.7 A	23.8 A	27 A	31.8 A								
Max. output current	7.9 A	9.5 A	12.7 A	14.3 A	15.9 A	19.1 A	20.7 A	23.8 A	27 A	31.8 A								
Power Factor	>0.99 (0.8 leading - 0.8 lagging)																	
THDi	<2%																	
Efficiency																		
Max. efficiency	98.3%		98.5%		98.6%		98.7%											
EU efficiency	97.7%		97.9%		98.0%		98.1%											
Protection																		
DC reverse-polarity protection	Yes																	
Short circuit protection	Yes																	
Output over current protection	Yes																	
Surge protection	Yes																	
Grid monitoring	Yes																	
Anti-islanding protection	Yes																	
Temperature protection	Yes																	
Integrated DC switch	Yes (PV2 Switch)																	
Integrated AFCI (DC arc-fault circuit protection)	Yes ⁽¹⁾																	
General Data																		
Dimensions (W*H*D)	310*563*219 mm																	
Weight	17.8 kg				18.8 kg		20 kg											
Topology	Transformerless																	
Self consumption (night)	<1 W																	
Operating ambient temperature range	-25 ~ +60°C																	
Relative humidity	0-100%																	
Ingress protection	IP66																	
Cooling concept	Intelligent redundant fan-cooling																	
Max. operation altitude	2000 m																	
Grid connection standard	AS/NZS 4777.2:2020, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530																	
Safety/EMC standard	IEC 62109-1/-2, IEC 61000-6-1/-2/-3/-4																	
Features																		
DC connection	MC4 connector																	
AC connection	Quick connection plug																	
Display	LCD																	
Communication	RS485, Optional: Wi-Fi, GPRS																	
Country of manufacture	China																	

(1) Activation required.